Wagon Gears manufactured by PMC in previous years are no longer available. Parts for the wagon gears may be ordered through the PMC office.

MODEL	706	806	896	1006	1206	1208	1286
Capacity	12,000 lbs	16,000 lbs	16,000 lbs	20,000 lbs	24,000 lbs	24,000 lbs	24,000lbs
Spindle Size	1 3/4" dia	2" dia.	2" dia.	2" dia.	2" dia	2 3/4" dia.	2 3/4" dia.
Hubs	Reinforced 6-bolt W888	Reinforced 6-bolt W888	Reinforced 6-bolt W888	Reinforced 6-bolt W783	Reinforced 6-bolt W783	Reinforced 8-bolt W821	Reinforced 6-bolt W783
Bearings	Tapered Roller	Tapered Roller	Tapered Roller	Tapered Roller	Tapered Roller	Tapered Roller	Tapered Roller
Bearing Diameter (inner)	1 1/2"	1 1/2"	1 1/2"	1 5/8"	1 5/8"	2"	1 5/8"
Bearing Diameter (outer)	2 5/8" dia.	2 7/8" dia.	2 7/8" dia.	2 7/8" dia	2 7/8" dia.	3 1/2" dia.	2 7/8" dia.
Reach Poles	2 5/8"	2 7/8" dia.	2 7/8" dia.	2 7/8 dia.	2 7/8" dia.	3 1/2" dia	2 7/8" dia.
Reach Length	8'	8'	8'	8'	8'	8'	8'
Optional Reach Length	2' Extension	2' Extension	2' Extension	2' Extension	2' Extension	2' Extension	2' Extension
Post Spacing	38" to 42"	38" to 42"	38" to 42"	38" to 42"	38" to 42"	38" to 42"	38" to 42"
Adjustable Tongue	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Axles	3x6x3/16 wall	4x8x3/16 wall	4x8x3/16 wall	4x8x3/16 wall	4x8x3/16 wall	4x10x3/16 wall	4x8x3/16 wall
Wheels	15x6 15x8	15x6 15x8 15x10 16x8	15x6 15x8 15x10 16x8	15x8 15x10 16x8 20x8	15x8 15x10 16x8	15x10/ 8-bolt W11C-16.1 W14C-16.1	15x8 15x10 16x8
Tread Width	72"	74"	90"	74"	74"	80"	80"
Turning Radius	7'10"	7'10"	9'	7'10" 9' w/10" or Larger Wheels	7'10" 9' w/10" or Larger Wheels	9'	8'6"
Rear Hitch	Standard	Standard	Standard	Standard	Standard	Standard	Standard